PATENT APPLICATION Serial Number: 09/184,600 Attorney Docket Number: STD 1716

#### REMARKS

This Amendment is filed responsive to an Office Action mailed June 14, 2001 with a shortened three-month response date.

By this Amendment, claims 1-33, 35-53 and 55-75 are pending. Claims 1-5, 7-10, 12, 13, 15-24, 26, 32-36, 39-58, 60-65 and 71-75 are allowed. Claims 6,11, 14, 25, 27-31, 37, 38, 59 and 66-70 are rejected because of informalities, which would be allowable upon clarifying for the record. The drawings are objected to, and correction is required.

By this Amendment, claims 6, 11, 14, 23, 25, 27, 29, 30, 37, 38, 59, 66, 67, 69 and 70 are amended. Furthermore, by this Amendment and a concurrent letter to the Official Draftsman (as to the Figures), Figure 5A is amended, and Figures 5C-5H (and the descriptions thereof) are added consistent with the specification as filed. No new matter is added.

Applicant wishes to call the Examiner's attention to the attached document entitled, "Amendment B--Changes Marked to Claims as Originally Filed," wherein all changes have been either stricken (removed verbiage) or underlined (added verbiage) as relate to the amendment of the originally filed patent application.

The drawings are objected to as failing to comply with 37 CFR 1.84(p)(4) because reference character "380" has been used to designate both scanner (37:22) and interface (37:25). By this amendment, the specification has been amended, and the drawing of FIG. 5A has been corrected to recite the interface (37:25) and 390. Correction has been made, and the objection to the drawings under 37 CFR 1.84(p)(4) has been overcome and traversed.

The Examiner objected to the drawings under 37 CFR 1.83(a), stating that "the drawings must show every feature of the invention specified in the claims." The Examiner states that "The claimed functional steps (claims 21-25, 34-37, 44-47, 50-53, 55-56, 61-71 and 75). The drawings show claimed structure, but there is a lack of illustration in the drawings for the claimed functionality. This is neither a written description nor an enablement issue, but rather, it pertains to a rule for illustrating to the public the claimed invention."

Attorney Docket Number: STD 1716

By this Amendment, certain ones of the drawings (Figure 5A) and respective portions of the specification have been amended and Figs. 5C-5H have been added (and respective portions of the specification have been amended) to further illustrate the claimed functionality responsive to the Examiner's objection. No new matter has been added.

While being responsive to the Examiner's objections, it is respectfully submitted that the drawings as originally filed show the features of the invention specified in the claims. Figures 3, 4, 6, and 10, and the description thereof within the specification (e.g., see page 16, lines 19-24, page 24, lines 22-23 and page 39, lines 9-17) provide both support in the drawings and the specification for the mapping of poses...emotional functions, as in, inter alia, claim 31 and claims 40-41, 44-45, and 48-50. Additionally, support for claims 40-41, 44-45, and 48-50 are provided in Figures 4C and 4D and the description thereof in the specification. Furthermore, Figures 1A and Tables I, II, and III and the description thereof in the specification, provide illustration in the drawing and related description, of the features of the invention specified in the claims 31, 44, 45 and 50 for which the drawings are objected to.

Figure 3 of the present application details the mapping of game display functions to the image data packets. Furthermore, Tables I, II, and III, in conjunction with the Figures 1A and 1B, provide additional structure in the drawings to show the features of the invention specified in the claims. The mapping of poses, as in claim 31, is additionally detailed in Figure 6, and the description thereof (see elements 1060, 1070, and 1080 of Figure 6). For example, at page 39, line 9, discussing step 1060, the specification states that "a decision is made to select poses." If yes, (step 1080)..."poses are selected, mapping data and formatting is generated."

It is respectfully submitted that all bases of objection of the drawings under 37 CFR 1.83(a), as to claims 21-25, 34-37, 44-47, 50-53, 55, 56, 61-71 and 75, have been overcome and traversed for the reasons as discussed above. No new matter has been entered.

Claims 6, 11, 14, 25, 27-31, 37, 38, 59 and 66-70 are objected to because of informalities. It is respectfully submitted that "mapping signals" are distinct from, and not redundant for, "integration control signals" as in claim 14 (amended). It is further respectfully submitted that a

PATENT APPLICATION
Serial Number: 09/184,600
Attorney Docket Number: STD 1716

"semiconductor device" is patentably distinct from, and not redundant for, "magnetic storage device." For support in the treatises, see for example, "Electronic Engineers Handbook," ©1975, 1st Edition, pp. 6-11, Section 6, "Properties of Materials," semiconductor is listed separately from magnetic; Section 23, "Electronic Data Processing," "Storage Methods, Devices, Circuits," semiconductor memories (pg. 55) are separately listed from Magnetic Storage (pp. 58-63). Copies of title pages and cited pages are attached herewith as a courtesy.

By this Amendment, Claims 6, 11, 14, 23, 25, 27, 29, 30, 37, 38, 59, 66, 67, 69 and 70 have been amended to overcome all bases of objection as set forth in paragraph 8 of Paper No. 15, Office Action dated June 14, 2001.

All bases of objection have been responded to and overcome by this Amendment, and the concurrent submission of revised drawings, a courtesy copy of which is enclosed herewith for the Examiner. It is respectfully submitted that the application is in proper form for allowance of all claims.

Early and favorable consideration of the amended application is respectfully requested, taking the form of allowance of all pending claims as amended.

Applicant's attorney thanks the Examiner for his time and courtesy in providing two telephone interviews and in providing an Examiner's Amendment and Summary thereof. As one addition to the Examiner's Summary dated June 7, 2001, Applicant wishes to note that claims 67 and 69, as amended, are consistent, and further note these claims cover any structure for providing the respective display presentation, and that the claim amendment, have been made to clarify this and responsive to the Examiner's objections.

A copy of the International Search Report has been previously faxed to the Examiner. However, enclosed herewith is a hard copy of said Report.

PATENT APPLICATION
Serial Number: 09/184,600
Attorney Docket Number: STD 1716

The Examiner is invited to communicate directly with the undersigned via phone as would be of assistance to expediting prosecution of this matter.

Respectfully submitted,

David H. Sitrick

Attorney for Applicant Registration No. 29,349

September 13, 2001

SITRICK & SITRICK 8340 N. Lincoln Ave., Suite 201 Skokie, IL 60077

Telephone Number: (847) 677-4411 Facsimile Number: (847) 677-4656

#### IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant:	David H. Sitrick	
_	Hear Image Integration and	)
For:	User Image Integration and Tracking for an Audiovisual	)
	System and Methodology	)
		)
Serial Number:	09/184,600	)
Filed:	November 2, 1998	)
		)
Examiner:	M. Sager	)
Art Unit:	3713	)
	3713	)
Attorney Docket:	STD 1716	)

#### AMENDMENT B-CHANGES MARKED TO CLAIMS AS ORIGINALLY FILED

- 6. (Amended) The system as in claim 5, wherein the storage medium is comprised of at least one of a videotape, a floppy disk, a compact disk, a digital video disk, other magnetic storage, other digital storage, a photographic print, and a computer image printout.
- 11. (Amended) The system as in claim 1, wherein at least one of the source of the first video image signal and the source of the user image signal is comprised of at least one of <u>an interface</u> with a modem, a CD-ROM, a DVD cartridge, a floppy disk, a smart card, magnetic storage, optical storage, and semiconductor storage.
- 14. (Amended) The system as in claim 13, wherein the external image signal is at least one of an analog signal, a digital signal, a broadcast video signal, signal parameter data, video image data, <u>digital</u> audio data, <u>and integration</u> control signals, <u>and mapping signals</u>.
- 23. (Twice Amended) The method as in claim 21, wherein the tracking data is signals are comprised of at least one of manually generated tracking data, automatically generated tracking data, and motion-capture data, wherein said tracking data is derived from the video signals and is representative of at least one of a plurality of defined actor positions. of the recognizable video



Attorney Docket Number: STD 1716

presentation of the respective selected character functions within each of the respective background images.

- 25. (Amended) The method as in claim 24, wherein the ancillary data is comprised of at least one of a background scene, a sequence of background scenes forming one of a video and an audiovisual presentation, hairstyle, facial hair, removal of hair, clothing, hair accessories, clothing accessories, hair color, facial cosmetic makeup, weapons, glasses, and tools. other props.
- 27. (Amended) The system as in claim 26, wherein the visual display presentation is representative of the image of a person, and wherein the ancillary attributes are further comprised of at least one of colors, lighting, clothing, other attire, hairstyle, hair color, removal of specified hair, addition of hair to a specified area of the image of a person, hair accessories, non-jewelry clothing accessories, facial accessories, jewelry, glasses, applied cosmetics, tools, and weapons.
- 29. (Twice Amended) A system for user creation and storage of user image signals, comprising:

apparatus for generating user image signals for a plurality of poses of a same user's user image;

storage apparatus; and

apparatus for formatting the user image signals and storing the formatted user image signals as digital data in the storage apparatus;

apparatus providing display signals for a display presentation comprising a plurality of background images representative of a plurality of background images of which at least two of which are comprised of a recognizable video presentation within the background images, associated with a common character function, wherein recognizable video presentation of the respective selected character function has respective position within the respective ones of the background images and respective predefined character function pose characteristics uniquely associated with the respective ones of the background images;



Attorney Docket Number: STD 1716

wherein the recognizable video presentation is comprised of a plurality of poses utilized in respective ones of a plurality of the background images;

means for selecting one of the character functions;

apparatus for mapping the user image signals for different ones of the poses therefor with each of the respective poses for the recognizable video presentation of the respective selected character functions within the respective background images of the video presentation, responsive to the respective position and the respective pose characteristic.

- 30. (Amended) The system as in claim 29, wherein the plurality of poses are at least one of front facial view, side facial view, top facial view, smiling, frowning, happy, sad, upset, angry, shy, frustrated, other facial expressions, sitting, standing, kneeling, jumping, and lying down.
- 37. (Twice Amended) The method as in claim 34, wherein the customized image is at least one of a video image, an audio sequence, and an audiovisual image, and a movie.
- 38. (Amended) The system as in claim 1, wherein the background image is further comprised of at least a portion of a person;

wherein the user image is representative of at least one of facial <u>expression</u> features, <u>predefined image data</u>, voice data, <u>arrangement of hair</u>, <u>style, mustache, beard, hair addition of hair to a selected part of the portion of the person</u>, color <u>of hair</u>, hair accessories, hair removal <u>of hair from a selected part of the portion of the person</u>, tools, instruments, clothing, accessories, and facial cosmetic makeup.

- 59. (Twice Amended) The system as in claim 58, wherein the display presentation is provided for at least one of a video display, an audiovisual display, a movie, a television broadcast display, a computer generated display, and a video game display.
- (Twice Amended) The stored audiovisual presentation as in claim 65, wherein the non-volatile form is one of video tape, semiconductor storage memory, a computer disk, a compact disk (CD), optical storage, and magnetic storage, and data for computer stored on any medium.



Attorney Docket Number: STD 1716

67. (Twice Amended) A method of providing a display presentation, the method comprising:

providing an audiovisual display presentation responsive to stored audiovisual

content produced by the process of:

providing user data;

providing a predefined source, wherein the source comprises audiovisual program content representative of a plurality of background images of which at least two of which are comprised of a common character function therewithin having a recognizable video presentation within respective ones of the background images, and, other program data;

selecting a portion of the audiovisual program content for the recognizable video presentation of a selected character function responsive to the other program data, as a selected portion for user data associative integration;

integrating the user data with the selected portion responsive to the other program data;

providing a modified output content in an audiovisual format responsive to the integrating wherein the user data is associated into the selected portion of the audiovisual program content.

- 69. (Twice Amended) The method as in claim 67, wherein the step of providing an audiovisual display presentation is one of provides for at least one of a video display, an audiovisual display, a projected movie display, a broadcast television display, a computer generated display, and a video game generated display.
- 70. (Twice Amended) The method as in claim 67, wherein the step of storing the modified output content uses at least one of a video tape, a magnetic storage, semiconductor storage, memory, a computer disk, a compact disc (CD), a digital versatile disc (DVD), and optical storage disc.



# ELECTRONICS ENGINEERS' HANDBOOK

# DONALD G. FINK, Editor-in-Chief

Executive Director and General Manager, Institute of Electrical and Electronics Engineers (Ret.);
Formerly Vice President—Research, Philco Corporation,
President of the Institute of Radio Engineers,
Editor of the Proceedings of the IRE;
Member, National Academy of Engineering;
Fellow of the Institute of Electrical and Electronics Engineers;
Fellow of the Institution of Electrical Engineers (London);
Eminent Member, Eta Kappa Nu

## ALEXANDER A. McKENZIE, Assistant Editor

Contributing Editor, IEEE Spectrum,
Formerly Senior Editor, Electronics,
Editorial Manager, McGraw-Hill Book Company,
Member of the Technical Staff, M.I.T. Radiation Laboratory;
Senior Member, Institute of Electrical and Electronics Engineers

#### First Edition

# McGRAW-HILL BOOK COMPANY

New York St. Louis San Francisco Auckland Düsseldorf Johannesburg Kuala Lumpur London Mexico Montreal New Delhi Panama Paris São Paulo Singapore Sydney Tokyo Toronto Library of Congress Cataloging in Publication Data

Fink, Donald G
Electronics engineers' handbook.

1. Electronics—Handbooks, manuals, etc. I. Title. TK7825.F56 621.381'02'02 74-32456 ISBN 0-07-020980-4

Copyright © 1975 by McGraw-Hill, Inc. All rights reserved. Printed in the United States of America. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of the publisher.

1234567890 QBQB 784321098765

The editors for this book at McGraw-Hill were Harold B. Crawford, Robert E. Curtis, and Robert Braine, and the production supervisor was Stephen J. Boldish. It was set in Times Roman by Rocappi/Lehigh, Inc.

It was printed and bound by Quinn & Boden Company, Inc.

Contributors .....Preface .....

#### Section 1. Basic

Elementary partic nomena; emission time-varying phe energy, acoustic a symbols

#### Section 2. Mat Electronics Engir

Differential and matrixes; Boolea

#### Section 3. Circui

Circuit concepts connections and theorems

#### Section 4. Inforr

Concepts, source channel, noise a:

#### Section 5. Syste

Definitions and

#### Section 6. Propo

Conductive and electron-emittin

#### Section 7. Discr

Resistors, capac ductor devices. fluidic devices;

55983

# CONTENTS

Contributors ix Preface xiii
Section 1. Basic Phenomena of Electronics1-1
Elementary particles, quanta and photons, energy levels, states of matter, chemical phenomena; emission, transport, control and collection of charged particles; steady-state and time-varying phenomena; dielectric, magnetic, and electromagnetic phenomena; radiant energy, acoustic and optical phenomena; human hearing and vision; definitions, units, and symbols
Section 2. Mathematics: Formulas, Definitions, and Theorems Used in Electronics Engineering2-1
Differential and integral calculus; series and expansions, transforms, probability, matrixes; Boolean algebra and symbolic logic
Section 3. Circuit Principles3-1
Circuit concepts and functions; lumped-constant and distributed circuits; network inter- connections and switching; magnetic and dielectric circuits; glossary of criteria, laws, and theorems
Section 4. Information, Communication, Noise, and Interference4-1
Concepts, sources and measures of information; codes and coding; the communications channel, noise and interference
Section 5. Systems Engineering5-1
Definitions and concepts; exterior and interior system design; human factors; techniques
Section 6. Properties of Materials6-1
Conductive and resistive, dielectric and insulating, magnetic materials; semiconductors; electron-emitting, radiation-emitting materials; optical and photosensitive materials
Section 7. Discrete Circuit Components7-1
Resistors, capacitors, inductors, transformers, electron tubes, cathode-ray tubes, semiconductor devices, transistors; batteries; ferromagnetic, ferroelectric, piezoelectric devices; fluidic devices; modular assemblies; relays, switches, insulators

bert E. Curtis,

55993

9

awn, N.J., Oxford Univerty Theory, pp. 181-186, in ocesses"; New York, John ng Workshop Notebook"; McGraw-Hill Book Comndations of Optimization"; ie FORTRAN Language"; to Using SIMSCRIPT";

Jnified Approach"; Engle-

nology"; New York, John

# SECTION 6

# PROPERTIES OF MATERIALS

ILAN A. BLECH Associate Professor, Department of Materials Engineering, Technion-Israel Institute of Technology, Haifa

### CONTENTS

Numbers refer to paragraphs

	Plastics
onductive and Resistive Materials	Fillers
	t aminates 95-97
onductivity 3 esistivity 8	Plastic Films, Foams, and 98
esistivity	Paper 100
hermal Effects	Wood
pecific Heat	Fabrics 102
tress	Mica 103
train	Ceramics 104
ihear 27	Ferroelectric Ceramics 105
Shear 27 Compressibility 29 Hardness 31	Piezoelectricity 106
Hardness	Electrolytic Films 107
Fatigue	Glass 108
Creep 40 Equilibrium Phase Diagrams 41	Fused Quartz and Silica 109
Equilibrium Phase Diagrams 41 Diffusion 42	Fused Quartz and Silica 109 Glass Ceramics 110 Thick-Film Dielectrics 110
Diffusion 42 Electromigration 44-51	
Electromigration 44-51	
Electromigration	Bibliography
Carrier Conductor Materials	
	114
Special Conductors 52 Copper	Magnetic Field
Aluminum 54	Magnetic Pole Suchstill
Silver         55           Gold         56	Magnetic Moment
Gold	Magnetic Flux Density 117
Gold	Permeability 118
Palladium 58	Susceptibility 119
Nickel	Magnetic Flux 120
	Magnetic Energy 121
Molybdenum 61	Classification of Magnetic 122
Sintered Materials 63 Contact Materials 65	Magnetization of Performance 123
Contact Materials 63	Ferromagnetic Domains 124
Fusible Alloys 66	Fnergy Product Curve 125
Resistance Metals 66 Carbon 66	Hysteresis Losses
Carbon 6	6 Eddy Current Losses
Carbon 60 Soldering Alloys 66 Conductive Coatings and Films 7	Total Core Losses 128
Conductive Coatings and Time	Demagnetizing Pactor 129
Shielding	1 Dermeability of Performance 130
Radar Absorbing Materials	a c
Bibliography	Magnetostriction
Biologia projekt	Materials
Dielectric and Insulating Materials	Specific Magnetic Materials 136 79 Retentive and Nonretentive Materials 136
Permittivity	70 Retentive and Nonretentive Materials
Permittivity	
Electric Polarization Dielectric Constant	80 Nonretentive Magnetic Materials
Dielectric Constant	81 137 87 Iron 138
Conduction in Dielectrics	87 Iron
Breakdown Thermal Properties	88 Iron-Silicon Steels 136 89 Iron-Cobalt Alloys 130 130 130 130 130 130 130 130 130 130
Thermal Properties	89 Iron-Cobalt Alloys
Materials	Iron-Aluminum and Iron-Aluminum-Sincon  14  Alloys
Specific Dielectric and Insulating Materials	
Gases	71. 10
Liquius	( )

#### PROPERTIES OF MATERIALS

Ferrites	Specific Electron-emitting Materials
Spinels	Thermionic Emitters
Hexagonal Ferrites	Pure-Metal Emitters
Garnets	Monolayer Emitters
Retentive Magnetic Materials	Oxide Emitters
Retentive Materials	Compound Emitters
Martensitic (Quench- and Work-hardened)	Alloy Emitters
Alloys	Secondary Electron Emitters 20
Precipitation-hardened Alloys 149	Photoelectric Emitters
Ordered Alloys	Metallic Emitters
Fine-Particle Magnets	Semiconductor Emitters
Bibliography	Silver-Oxygen-Cesium Emitters 21
	Ultraviolet-sensitive Photocathodes 21
Semiconductor Materials	Special Cathodes 21
Elemental and Compound Semiconductors 153	Bibliography
Energy Bands and Gaps 154	
Intrinsic and Extrinsic Semiconductors 155	Radiation-emitting Materials
Charge Transport	Blackbody Radiation
Carrier Concentration in Intrinsic	Relative Luminosity and Luminous Efficiency 21
Semiconductors	Coherent and Incoherent Radiation 21
Donor and Acceptor Impurities	Radiation from Heated Solids 21
Carrier Concentration in Extrinsic	Radiation from Combustion
Semiconductors	Radiation from Excited Gases, Vapors, and
Impurity Energy Levels         160           Surface States         161	Plasmas
Conduction in Semiconductors	Luminescence
Carrier Diffusion	Stimulated Emission (Laser Radiation) 223
Carrier Generation and Recombination 164	Specific Radiation-emitting Materials
High-Energy Irradiation Effects 165	
Hall Effect	Metal Filaments
Photoconductive Effect 167	Noble Gases
Thermoelectric Effect	Sodium Vapor
Acoustoelectric Effect	Mercury Vapor
Junction Phenomena	Phosphors
	Solid-Laser Materials
pn Junctions	Liquid-Laser Materials
Metal-Semiconductor Junctions	Gas-Laser Materials
Tabulated Data	Chemical Lasers
Specific Semiconductors	Bibliography
Silicon	Optical and Photosensitive Materials
Germanium	
ſin	Index of Refraction
Diamond and Graphite	Dispersive Power
Selenium	Birefringence
Silicon Carbide	Dichroic Crystals
Gallium Arsenide         180           ndium Antimonide         181	Transmittance and Reflectance
Gallium Phosphide	Transmission and Reflection Density 240
somorphous Systems	Exposure
Sadmium Compounds	Characteristic Curve of Emulsions 242
ead Compounds	Spectral Sensitivity of Photographic Emulsions . 243
Bismuth Telluride	Image Formation on Emulsions
Metal Oxides	Developing and Fixing
Organic Semiconductors	Reversal Process
Amorphous Semiconductors 189	Specific Optical and Photosensitive Materials
Sibliography	
	Optical Glasses
dectron-emitting Materials	Filters
Vork Function and Surface-potential Barrier 191	Mirrors
hermal Emission from Metals 192	Light-sensitive Glasses
chottky Effect	Polarizing Materials
rield Emission	Monochrome Film Emulsions
econdary Emission	Other Recording Media
nergy Distribution of Secondary Electrons 196  Iffect of Surface Contamination 197	Color-Film Emulsions
ffect of Angle of Incidence	
hotoemission	Bibliography
hotoelectric Efficiency (Yield) 200	References

1. Volume electrical curr

where  $\sigma = vo$ (A/m<sup>2</sup>), and . of current der The volum

where  $G = c_i$ section (m<sup>2</sup>). 2. Mass C

where  $\sigma_m = n^2$ and  $m = con^2$ 3. Volume current densit

where  $\rho = res$ (V/m). The between the  $v_i$ 

where R = resTable 6-1 lists resistivity of a 4. Mass R

where  $\delta = ma$  (m).

5. Internat copper at 20°C resistivity of al 10 - 8 Ω · m.

### SECTION 23

## **ELECTRONIC DATA PROCESSING**

RX

RODGER L. GAMBLIN Area Manager, Chemical Products Development, Office Products Division, IBM Corporation

WILLIAM P. HEISING Senior Programmer, Advanced Systems Architecture, Systems Development Division, IBM Corporation

GERHARD E. HOERNES IBM Scholar, Advanced Education, Systems Products Division, IBM Corporation; Member, IEEE

#### CONTENTS

Numbers refer to paragraphs

Principles of Data Processing		Algebraic Properties of Binary Variables	39
Definition of a Computer	1	Minimization of Boolean Functions	40
Desk Calculator	2	Minimization in Code Translation	41
Stored-Program Methods	3	Sequential Circuits	42
Internal Modification of Stored Programs	4	Circuit Realization with Relays	43
Memory, Processing, and Control Units	5	Circuit Realization with Electron Tubes	44
Historical Background	6	Circuit Realization with Semiconductor Devices	45
Digital Computation Functions	7	Transistor Logic Circuits	46
	8	Representative Computer Circuits	47
Data Processing Speed and Integrity	9	Design and Packaging of Computer Systems	48
Binary and Decimal Numbers		Design Automation	49
Internal and External Information	10	Other Logic Elements	50
Error-Correction Codes	11	Threshold Logic	51
Boolean Functions	12	The sales and could be sales as a	٠.
Logical-Function Realization	13	Storage Methods, Devices, and Circuits	
Electronic Realization of Logical Functions	14	-	
Levels of Operation in Data Processing	15	Functions of Storage	52
Programming with Instruction Sets	16	Random Access vs. Serial Storage	53
Numerical Methods	17	Nomenclature of Storage Devices	54
Information Flow and the Job Stream	18	Magnetic-Core Storage	55
Types of Computer Systems	19	Random-Access Selection Methods	56
Internal Organization of Digital Computers	20	Semiconductor Memories	57
Analog Computation	21	Thin-Film Magnetic Storage	58
Amplitude and Time-Scale Compensation	22	Magnetic Drums	59
Analog-Computer Components	23	Storage on Thin Magnetic Media	60
Function Generation	24	Magnetic-Disk Recording	61
Hybrid Systems	25	Characteristics of Drum and Disk Systems	62
		Magnetic-Tape Systems	63
Number Systems, Arithmetic, Codes, and		Read-Only Storage Systems	64
Numerical Methods		Read-Write Optical Storage	65
Representation of Numbers	26	Electrostatic Storage	66
Number-System Conversions	27	Cryogenic Devices	67
Number-System Efficiency	28	Magnetic-Bubble Devices	68
Binary-Arithmetic Operations	29	Amorphous Semiconductor Devices	69
Subtraction by Complement Addition	30	Storage Organization	70
Floating-Point Numbers	31	Look-ahead and Partition Methods	71
Numeric and Alphanumeric Codes	32	List Stores	72
Error Detection and Correction Codes	33		-
Polynomial Codes	34	Input-Output Equipment and Systems	
Numerical Methods of Computation	35	I . O (I/O) F	
reduction in computation	33	Input-Output (I/O) Equipment	73
Boolean Operations, Circuit Realizations,		I/O Configurations	74
Interconnections, and Computer Organization		I/O Memory-Channel Methods	75 76
Symbolic Louis and the Systemial Coloring	16	Channel Functions	
Symbolic Logic and the Sentential Calculus	36 37	Channel Attachment	77
Boolean Algebra	38	Card Unit Record Equipment	78
boolean runctions; minterms and maxterms	38	Key-to-Tape and Key-to-Disk Systems	79

In Fig. 23-69b each storage cell contains a two-way AND, e.g., as in magnetic cores. In this system each of two lines is energized to select one core, and instead of m interrogation lines,  $2m^{1/2}$  lines are used in the selection scheme. In Fig. 23-69c, each storage cell is associated with a three-way AND. The interrogation lines required are  $3m^{1/2}$ . In the final case (Fig. 23-69d), a six-way AND is used with each storage cell and only  $6m^{1/2}$ , or 12, interrogation lines are required. In the latter case, the number of drive lines is minimized, and no decoding function is required externally to the storage system.

57. Semiconductor Memories. Figure 23-70 shows a basic circuit for realization of a storage function using a bipolar transistor circuit. The select line performs the function of selection, and if selected, the sense and write lines can be used for the read or write function. This bipolar transistor store is NDRO, volatile, and random access.

Figure 23-71 shows a static storage cell that uses FET devices. Selection is accomplished through x and y lines that open gates to the sense and reset lines. The system is NDRO, volatile, and random access.

Bipolar circuits in a storage system are generally faster, more wasteful of power, and more expensive than FET devices. The difference in cost arises primarily because bipolar devices require more complex processing steps in manufacture.

58. Thin-Film Magnetic Storage. Figure 23-72 shows a thin magnetic film, such as Permalloy, with two labeled hysteresis loops. An isotropy is present in the film if it is plated or evaporated on a support in the presence of an external magnetic field. This isotropy defines an easy and hard axis of magnetization. If the shape of the film is long and thin (to prevent pole demagnetization), the magnetization will lie along the easy axis in either of two directions and a single domain will be found in the film. In the easy-axis direction the hysteresis loop of the film tends to be square (Fig. 23-72b); in the hard-axis direction the loop is nearly linear. The square hysteresis loop in the easy-axis direction permits nonvolatile binary storage.

Figure 23-73 shows operation of a storage array using Permalloy plated on conductive wires. The easy axis is in the direction of the wires, and information is stored at the intersections of a wire with each sense line. The information state is determined by the direction of the magnetization at each intersection. Current in the wire rotates the




Fig. 23-70. A bipolar transistor storage cell. Storage is accomplished by means of a cross-coupled transistor flip-flop. The normal state of the select line is such that the output is below detection levels in either state of the flip-flop. When the cell is selected, the sense output becomes sufficiently positive for detection if T1 is off. Similarly the select line needs to be positive while writing; otherwise T3 and T4 remain off.




Fig. 23-71. An FET storage cell.  $T_5$  and  $T_6$  are FETs used as load resistors while  $T_7$  is a two-way AND circuit that connects the cell to the bit and sense lines when selection occurs.  $T_1$  and  $T_2$  form a cross-coupled flip-flop. The state when  $T_2$  is on represents a 1. The sense line is used for set and the bit reset line for reset.

Fig. 23-Permall magneti along the in the h

Fig. 2' of the currer direct cores. In terrogation age cell is in the final  $n^{1/4}$ , or 12, ninimized, tation of a unction of

omplished NDRO.

and more ar devices

such as t is plated isotropy d thin (to ter of two ction the the loop avolatile

nductive d at the d by the ates the

efect

tre ay nd

 $T_2$ zn




Fig. 23-72. Magnetic storage properties of a ferromagnetic film. When a magnetic film (a), such as Permalloy, is deposited in the presence of a magnetic field, the film develops a preferred (easy) axis of magnetization. If the film is thin and long in the easy-axis direction, the magnetization of the material along the easy axis can occur in either of two directions, with a square hysteresis loop (b). The loop (c) in the hard direction is not square.




Fig. 23-73. Storage system using wires plated with magnetic material. The easy axis is in the direction of the wires, so that the film magnetization at each bit location is either parallel or antiparallel to the read-current direction. When a read current is applied, the magnetization is rotated into the hard-axis direction, causing coupling to the sense lines. The signal on the sense line is either positive- or negative-going, depending upon the prior direction of the magnetization vector.